

SEKUR FT

PHOTOCELLS



FT32



FT42



FT42B



RP25K

CODE	DESCRIPTION
FT32	Set of photocells for external use and flush mounting (1 set)
FT42	Set of photocells for external use adjustable 180°, for small pillars (1 set)
FT42B	Set of photocells for external use adjustable 180°, for small pillars, battery powered (1 set)
RP25K	Set of reflective photocell for external use complete with mounting brackets, rain and anti-condensation covers (1 kit)

		FT32	FT42	FT42B	RP25K
ELECTRICAL DATA					
power	Vac	12-24	12-24	12-24	18-30
	Vdc	12-35	12-35	12-35	10-40
range	m	25	25	20	12
consumption rx	mA	27	27	35	-
consumption tx	mA	10	10	0,04	30
relay contacts max supply	A	1	1	1	0.5
GENERIC DATA					
protection degree	IP	54	54	54	65
dimensions (L - D - H)	mm	80 - 33 - 90	35 - 35 - 110	35 - 35 - 110	44 - 39 - 86
operating temperature	°C	-20 + 55	-20 + 55	-20 + 55	-25 + 60

PLUS

Photocell activates an adaptative temporised mode, in case of frequent dimming or darkening, to avoid false obstacles detection.

Adjustable range (FT series)

High degree of protection (IP65), easy adjustment of optical sensor, LED alignment indicator, polarised optical filter system.

Immune to external light sources. Highly reliable and practical with all mounting accessories (RP25K)