



automation for sliding gates and
outdoor led lighting



**MADE IN
ITALY**

SUN series for sliding gates

FASTLINE



SUN5024 FAST - SLIDING GATE OPERATOR UP TO 500 Kg GATES, 24 Vdc

- fast opening and closing speeds up to 40 cm/sec
- integrated LED lighting on the cover, compatible with Night Light System garden lighting (NLS)
- extremely silent operations thanks to the use of high performance materials
- smooth operations, soft start & soft stop
- safe, integrated obstacle detection
- optional back-up battery
- robust die casted and powder coated aluminium body
- easy to operate emergency release mechanism
- compatible with solar system, no 240V power required at the gate
- designed and Made in Italy



SUN11024 - SLIDING GATE OPERATOR UP TO 1,100 Kg GATES, 24 Vdc

- opening and closing speeds up to 20 cm/sec
- integrated LED lighting on the cover, compatible with Night Light System garden lighting (NLS)
- extremely silent operations thanks to the use of high performance materials
- smooth operations, soft start & soft stop
- safe, integrated obstacle detection
- optional back-up battery
- robust die casted and powder coated aluminium body
- easy to operate emergency release mechanism
- compatible with solar system, no 240V power required at the gate
- designed and Made in Italy



SUN4224 - SLIDING GATE OPERATOR UP TO 400 Kg GATES, 24 Vdc

- opening and closing speeds up to 26 cm/sec
- extremely silent operations thanks to the use of high performance materials
- smooth operations, soft start & soft stop
- smart and safe electronics, integrated obstacle detection
- robust die casted and powder coated aluminium body
- easy to operate emergency release mechanism
- optional back-up battery
- compatible with solar system, no 240V power required at the gate
- designed and Made in Italy

		SUN5024F	SUN11024	SUN4224
MECHANICAL DATA	cm/s	40*	20*	26*
speed	Nm	23	38	18
torque	%	80	80	80
working cycle				
ELECTRICAL DATA		14AF	14A	CT102 24
control board	Vac	230	230	230
power	A	1,3	1,3	1,2
consumption	W	300	300	250
absorbed power	µF	-	-	-
capacitor	°C	-	-	-
thermoprotection		na.	na.	na.
GENERIC DATA				
protection degree	IP	44	44	44
dimensions (L - D - H)	mm	330 - 210 - 300	330 - 210 - 300	330 - 210 - 300
weight	kg	13	13	12
working temperature	°C	-20 + 55	-20 + 55	-20 + 55
gate maximum weight	Kg	500	1100	400

* variable according to the gate weight



Integrated LED (SUN5024F - 11024)




Elegant design




Ergonomic release mechanism



Silent and robust gear reduction




Built-in smart electronics



Stylish & colourful water resistant multi-channel remotes





KEY AUTOMATION AUSTRALIA

Unit 2 - 11 Cooper Street
Smithfield NSW 2164
AUSTRALIA
Ph. 1300 001 KEY - 1300 001 539
info@keyautomation.com.au
www.keyautomation.com.au



follow us:     